

HeroEE 2

POWER STATION

2009.6Wh

1000W



Light

20W $\approx$ 85h



Fan

30W $\approx$ 57h



Fridge

100W $\approx$ 17h



CCTV

40W $\approx$ 42h



More Capacity
Higher Power



Installation-Free



Ultra-Long Life



Maintenance-Free



AC Output Power 1000W

AC Output 



Grid 1000W

AC Input 



Solar Panel 450W

PV Input 



PRODUCT DETAILS

Model	HeroEE 2
Battery Type	LiFePO4
Battery Capacity	2009.6Wh
Cell Capacity	314Ah
Battery Cycles	11000 cycles@(25°C, 100%DOD, 0.5P, @70%SOH)
AC Output Power	1000W
AC Output Voltage	200-240[VAC](Bypass Mode)/230[VAC](Inverter Mode), 50Hz/60Hz
AC Input Power	1000W
AC Input Voltage	200-240[VAC],50Hz/60Hz
Max. PV Input Power	450W
PV Input Voltage	12-50[VDC]
Max.PV Input Current	20A
Ingress Protection Level	IP20
Protection	AC Input Overvoltage/Undervoltage, AC Output Overvoltage/Overload/Undervoltage/OverCurrent/Short Circuit, Battery Cell High/Low Temperature/Overvoltage/Undervoltage/Short Circuit/Ovecurrent, PV Input Reverse Polarity/Overcurrent/Overload, Over Temperature
Operating Temperature	Charging: 0°C-40°C Discharging: -20°C-40°C
Storage Temperature	-20°C-60°C
Humidity	10%-90%
Net Weight	18.3kg
Dimensions	L285*W210*H311mm
Certification	CE, CB, UN38.3, IEC62619

*The above is for reference only, the specification sheet shall prevail.

Contact:

Tel:

<https://www.hero-ee.com>



Business Cooperation



website